# Freeform Search

---

**Database:**
US Pre-Grant Publication Full-Text Database
US Patents Full-Text Database
US OCR Full-Text Database
EPO Abstracts Database
JPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins

**Term:** L3 and ((electrode near2 lead) with (nickel or Ni))

**Display:** 20 **Documents in Display Format:** - **Starting with Number** 1

**Generate:** ○ Hit List ◉ Hit Count ○ Side by Side ○ Image

---

Search | Clear | Interrupt

---

## Search History

**DATE: Thursday, April 06, 2006**   Printable Copy   Create Case

| Set Name side by side | Query | Hit Count | Set Name result set |
|---|---|---|---|
| *DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=ADJ* | | | |
| L14 | L3 and ((electrode near2 lead) with (nickel or Ni)) | 43 | L14 |
| L13 | L4 and ((electrode near2 lead) with (nickel or Ni)) | 1 | L13 |
| L12 | L11 not l5 | 37 | L12 |
| L11 | L3 and ((current interrup$4 or limit or limit$3) same (electrode near2 lead)) | 118 | L11 |
| L10 | L3 and ((current interrup$4 or limit or limit$3) same notch) | 9 | L10 |
| L9 | L3 and ((current interrup$4 or limit or limit$3) same notch same (electrode near2 lead)) | 3 | L9 |
| L8 | L3 and ((current interrup$4 or limit or limit$3) with notch with (electrode near2 lead)) | 1 | L8 |
| L7 | L3 and (current interrup$4 or limit or limit$3) | 625 | L7 |
| L6 | L5 not l4 | 67 | L6 |
| L5 | L3 same (current interrup$4 or limit or limit$3) | 87 | L5 |
| L4 | L3 with (current interrup$4 or limit or limit$3) | 20 | L4 |
| L3 | L2 with (electrode or anode or cathode) near2 lead | 1113 | L3 |
| L2 | electrode (assembly or group) | 35586 | L2 |
| L1 | JP-10214614-$.did. | 2 | L1 |

# WEST Search History

Hide Items | Restore | Clear | Cancel

DATE: Thursday, April 06, 2006

| Hide? | Set Name | Query | Hit Count |
|---|---|---|---|
| | | *DB=PGPB,USPT,USOC,EPAB,JPAB,DWPI,TDBD; PLUR=YES; OP=ADJ* | |
| ☐ | L14 | L3 and ((electrode near2 lead) with (nickel or Ni)) | 43 |
| ☐ | L13 | L4 and ((electrode near2 lead) with (nickel or Ni)) | 1 |
| ☐ | L12 | L11 not l5 | 37 |
| ☐ | L11 | L3 and ((current interrup$4 or limit or limit$3) same (electrode near2 lead)) | 118 |
| ☐ | L10 | L3 and ((current interrup$4 or limit or limit$3) same notch) | 9 |
| ☐ | L9 | L3 and ((current interrup$4 or limit or limit$3) same notch same (electrode near2 lead)) | 3 |
| ☐ | L8 | L3 and ((current interrup$4 or limit or limit$3) with notch with (electrode near2 lead)) | 1 |
| ☐ | L7 | L3 and (current interrup$4 or limit or limit$3) | 625 |
| ☐ | L6 | L5 not l4 | 67 |
| ☐ | L5 | L3 same (current interrup$4 or limit or limit$3) | 87 |
| ☐ | L4 | L3 with (current interrup$4 or limit or limit$3) | 20 |
| ☐ | L3 | L2 with (electrode or anode or cathode) near2 lead | 1113 |
| ☐ | L2 | electrode (assembly or group) | 35586 |
| ☐ | L1 | JP-10214614-$.did. | 2 |

END OF SEARCH HISTORY